

HOSE REELS – MANUAL & AUTOMATIC REWIND



EMPTY & PRE-FITTED
FIRE HOSE
AIR & WATER
WASHDOWN

HOSE REELS - MANUAL



PRODUCT SPECIFICATIONS

FEATURES:

- Black powdercoated steel frame
- 3/4 inch Stainless Steel BSP Swivel
- Solid and sturdy construction

- 3/4 inch inlets and outlets
- Flat packed for easy shipment

Performer Steel Industrial Hose Reels

Complete with 3/4 inch Stainless Steel BSP Swivel.

Part Number	Hose Reel			
	BSP Port (Inches)	Inlet BSPF (Inches)	Outlet BSPF (Inches)	Approximate Reel Capacities
60-000-030-012	3/4 S/S Swivel	3/4	3/4	12 mm hose = 30 m
60-000-040-018	3/4 S/S Swivel	3/4	3/4	18 mm hose = 40 m
60-000-060-018	3/4 S/S Swivel	3/4	3/4	18mm hose = 60 m



A

PRODUCT SPECIFICATIONS

A. 34 metre Black Fire Hose on reel. Includes barrel nozzle & 1.5 metre feeder hose.

C. 34 metre Black Fire Hose on reel. Includes barrel nozzle & feeder hose.

B. 20 metre Yellow/Blue Safety Hose on reel. Includes barrel nozzle & 1.5 metre feeder hose.

Pre-fitted Hose Reels

Part Number	Reference	Fitted Hose					Hose Reel	
		ID (mm)	Length (m)	Max. WP psi (mPa)	Material	Temp (°C)	Inlet	Outlet
60-000-9040-018FH	A	19	34	145 (1.00)	PVC	60	Open	Barrel Nozzle
60-000-9040-018SY	B	19	20	145 (1.00)	PVC	60	Open	Barrel Nozzle
60-000-9060-018FH	C	25	34	145 (1.00)	PVC	60	Open	Barrel Nozzle



B



C



PRODUCT SPECIFICATIONS

FEATURES:

- Certified by SAI Global ASI221
- Reel includes 36 metre 19 mm black PVC Fire Hose and fittings for installation projects & factory builds.

- Hose size 19 mm
- Test pressure 2000 kpa & working pressure 1500 kpa
- Fixes to wall

Australian Standard Fixed Fire Hose Reel Kit

With years of development behind it this Australian Standard Fixed Hose Reel is widely regarded as one of the best and most reliable available on the Australian Market today.

Part Number	Fitted Hose					Fixed Hose Reel	
	ID (mm)	Length (m)	Max. WP (kPa)	Material	Min. Discharge Rate	Inlet	Outlet
60-050-036-012	19	36	1500	PVC	0.45 L/Sec	1" BSPF	Nozzle

HOSE REELS - AUTO REWIND WATER



PRODUCT SPECIFICATIONS

Retractable compressed air/water reels come supplied with a reinforced PVC hose in a blue casing. Spring rewind with operating pressure up to 1700 kPa (250 psi) reels have BSPF reel inlets and BSPM hose outlets. Complete with carry handle and mounting bracket.

FEATURES:

- Fully portable reel with carry handle
- 270° pivot and locking plate
- Impact resistant
- 10 year warranty

MacNaught Retractable Air & Water Auto Rewind Hose Reels

Includes hose and fitting attachments

Part Number	Fitted Hose					Hose Reel			
	ID (mm)	Length (m)	Max. WP psi (mPa)	Material	Temp (°C)	Inlet BSPF (Inches)	Outlet BSPM (Inches)	Weight (kg)	
60-200-AW2150	10	15	250	Reinforced PVC	60 -/+5	3/8	1/4	10	
60-200-AW2101	10	20	250	Reinforced PVC	60 -/+5	3/8	1/4	10	
60-200-AW2121	12.5	15	250	Reinforced PVC	60 -/+5	3/8	3/8	10	



PRODUCT SPECIFICATIONS

Retractable compressed air/water reels come supplied with a reinforced PVC hose in a red casing. Spring rewind with operating pressure up to 1700 kPa (250 psi) reels have a BSPF reel inlet and a BSPM hose outlet. Complete with carry handle and mounting bracket.

FEATURES:

- Fully portable reel with carry handle
- 270° pivot and locking plate
- Impact resistant
- 10 year warranty

MacNaught Retractable Air Auto Rewind Hose Reels

Includes hose and fitting attachments

Part Number	Fitted Hose					Hose Reel			
	ID (mm)	Length (m)	Max. WP psi (mPa)	Material	Temp (°C)	Inlet BSPF (Inches)	Outlet BSPM (Inches)	Weight (kg)	
60-200-AR2101	10	20	250	Superflex PVC	60	3/8	1/4	10	
60-200-AR2121	12.5	15	250	Superflex PVC	60	3/8	3/8	10	

The full MacNaught Washdown Auto Rewind range of Hose Reels, along with other ranges, are available from Powell Industrial. Please contact with your local branch for assistance.



macnaught

BUILT TO LAST SINCE 1948

Established in 1948 by Colin Macnaught, Macnaught Pty. Ltd. is a 100% Australian-owned company based in Sydney, which designs and manufactures a wide range of high quality equipment for the lubrication and fluid transfer industries including grease pumps and guns, oil pumps and guns, fuel pumps, hose reels and flow meters. These products are sold into the agricultural, industrial, automotive, mining, aviation and marine industries around the world.

Macnaught has built a strong reputation for designing and manufacturing innovative, high quality, durable products that are well supported with technical advice and service. Macnaught offers a 10 year warranty on most products and guarantees availability of spare parts for 10 years. Macnaught products are supported by a network of authorized service centres.



65 YEARS OF
PRECISION MANUFACTURING

RETRACTA®

AUSTRALIAN MADE FOR
OVER 25 YEARS

oilmaster® t-series™

MANUFACTURING IN
AUSTRALIA FOR OVER 20 YEARS



www.macnaught.com.au



HOSE REELS - AUTO REWIND WATER



PRODUCT SPECIFICATIONS

Retracta domestic garden water hose reel is a premium quality, strong and reliable reel, constructed using UV stabilised polypropylene, heavy duty rewind spring, quality swivel assembly, 12.5mm x 18mtr hose assembly and is supplied complete with mounting bracket and carry handle, fitted with a positive spring latch mechanism the hose can be latched every half metre.

FEATURES:

- Fully portable reel with carry handle
- 270° pivot and locking plate
- Impact resistant
- Corrosion and weather resistant construction
- Sealed and lubricated main spring for a virtually maintenance free service life
- 10 year warranty

MacNaught Retractable Domestic Garden Water Auto Rewind Hose Reel

Includes hose and fitting attachments

Part Number	Fitted Hose					Hose Reel		
	ID (mm)	Length (m)	Max. WP psi (mPa)	Material	Temp (°C)	Inlet	Outlet	Weight (kg)
60-200-DR2121	12.5	18	125	Reinforced PVC	60	Garden Tap Connection	Trigger Nozzle	10



PRODUCT SPECIFICATIONS

Retracta workshop water hose reel is a premium quality, strong and reliable reel, constructed using UV stabilised polypropylene, heavy duty rewind spring, quality swivel assembly, 12.5mm x 15m reinforced PVC hose assembly and is supplied complete with a steel mounting bracket and carry handle, fitted with a positive spring latch mechanism the hose can be latched every half metre.

FEATURES:

- Fully portable reel with carry handle
- 270° pivot and locking plate
- Impact resistant
- Corrosion and weather resistant construction
- Sealed and lubricated main spring for a virtually maintenance free service life
- 10 year warranty

MacNaught Retractable Workshop Water Auto Rewind Hose Reel

Includes hose and fitting attachments

Part Number	Fitted Hose					Hose Reel		
	ID (mm)	Length (m)	Max. WP psi (mPa)	Material	Temp (°C)	Inlet BSPF (Inches)	Outlet BSPM (Inches)	Weight (kg)
60-200-WR2121	12.5	15	250	Reinforced PVC	60	3/8	1/4	13

HOSSES

FITTINGS

PNEUMATICS

HOSE REELS

RUBBER

ACCESSORIES & CONSUMABLES

CHARTS & TABLES

HOSE REELS - AUTO REWIND WASHDOWN



PRODUCT SPECIFICATIONS

Retractable high pressure hot water hose reel is a premium quality, strong and reliable reel, constructed using UV stabilised polypropylene, heavy duty rewind spring, quality swivel assembly, 10mm x 12m reinforced rubber (SAE100R2) hot water hose assembly and is supplied complete with mounting bracket and carry handle, fitted with a positive spring latch mechanism the hose can be latched every half metre.

FEATURES:

- Fully portable reel with carry handle
- 270° pivot and locking plate
- Impact resistant
- Corrosion and weather resistant construction
- Sealed and lubricated main spring for a virtually maintenance free service life
- 10 year warranty

MacNaught Retractable High Pressure Hot Water Washdown Auto Rewind Hose Reel

Includes hose and fitting attachments

Part Number	Fitted Hose					Hose Reel		
	ID (mm)	Length (m)	Max. WP psi (mPa)	Material	Temp (°C)	Inlet BSPF (Inches)	Outlet BSPM (Inches)	Weight (kg)
60-200-HWP2101	10.0	12	3000	Reinforced rubber*	95	3/8	3/8	12

*(SAE100R2)



PRODUCT SPECIFICATIONS

Retractable cold water hose reel is a premium quality, strong and reliable reel, constructed using UV stabilised polypropylene, heavy duty rewind spring, quality swivel assembly, 12.5mm x 15m reinforced PVC cold water hose assembly and is supplied complete with mounting bracket and carry handle, fitted with a positive spring latch mechanism the hose can be latched every half metre.

FEATURES:

- Fully portable reel with carry handle
- 270° pivot and locking plate
- Impact resistant
- Corrosion and weather resistant construction
- Sealed and lubricated main spring for a virtually maintenance free service life
- 10 year warranty

MacNaught Retractable Cold Wash Auto Rewind Hose Reels

Includes hose and fitting attachments

Part Number	Fitted Hose					Hose Reel		
	ID (mm)	Length (m)	Max. WP psi (mPa)	Material	Temp (°C)	Inlet BSPF (Inches)	Outlet	Weight (kg)
60-200-CW2121	12.5	15	150	Reinforced PVC	60	3/8	Hose Nozzle	10



PRODUCT SPECIFICATIONS

Retractable hot wash reels come supplied with a reinforced rubber hose in red casing. Spring rewind with operating pressure up to 1400 kPa (200 psi) reels have a BSPF reel inlet and a BSPM hose outlet. Complete with carry handle and mounting bracket.

FEATURES:

- Fully portable reel with carry handle
- 270° pivot and locking plate
- Impact resistant
- Corrosion and weather resistant construction
- Sealed and lubricated main spring for a virtually maintenance free service life
- 10 year warranty

MacNaught Retractable Hot Wash Auto Rewind Hose Reels

Includes hose and fitting attachments

Part Number	Fitted Hose					Hose Reel		
	ID (mm)	Length (m)	Max. WP psi (mPa)	Material	Temp (°C)	Inlet BSPF (Inches)	Outlet BSPM (Inches)	Weight (kg)
60-200-HW2121	12	12	200	Reinforced Rubber	90	3/8	3/8	10

HOSE REELS - AUTO REWIND GAS & OIL



PRODUCT SPECIFICATIONS

Retracta coolant hose reel is a premium quality, strong and reliable reel, constructed using UV stabilised polypropylene, heavy duty rewind spring, quality swivel assembly, 12.5mm x 10m reinforced rubber hose assembly and is supplied complete with CCG-01 Coolant gun, mounting bracket and carry handle, fitted with a positive spring latch mechanism the hose can be latched every half metre.

FEATURES:

- Fully portable reel with carry handle
- 270° pivot and locking plate
- Impact resistant
- Corrosion and weather resistant construction
- Sealed and lubricated main spring for a virtually maintenance free service life
- 10 year warranty

MacNaught Retractable Coolant Auto Rewind Hose Reel

Includes hose and fitting attachments

Part Number	Fitted Hose					Hose Reel		
	ID (mm)	Length (m)	Max. WP psi (mPa)	Material	Temp (°C)	Inlet BSPF (Inches)	Outlet BSPM (Inches)	Weight (kg)
60-200-CR2121	12.5	10	375	Reinforced rubber	90	3/8	1/2	13



PRODUCT SPECIFICATIONS

Retracta high pressure grease hose reel is a premium quality, strong and reliable reel, constructed using UV stabilised polypropylene, heavy duty rewind spring, quality swivel assembly, 6mm x 10m reinforced high pressure rubber grease hose assembly and is supplied complete with a mounting bracket and carry handle, fitted with a positive spring latch mechanism the hose can be latched every half metre.

FEATURES:

- Fully portable reel with carry handle
- 270° pivot and locking plate
- Impact resistant
- Corrosion and weather resistant construction
- Sealed and lubricated main spring for a virtually maintenance free service life
- 10 year warranty

MacNaught Retractable High Pressure Grease Auto Rewind Hose Reel

Includes hose and fitting attachments

Part Number	Fitted Hose					Hose Reel		
	ID (mm)	Length (m)	Max. WP psi (mPa)	Material	Temp (°C)	Inlet BSPF (Inches)	Outlet BSPM (Inches)	Weight (kg)
60-200-GR2061	6.0	10	5000	Reinforced rubber*	95	1/4	1/4	13

*(SAE100R2)

Other quality hoses reels from MacNaught are available on request. Please contact your local Powell Industrial branch for assistance or visit www.macnaught.com.au to see the complete range then give us a call.



Industrial and Hydraulic Hose & Fittings

A CUT ABOVE THE REST.

FOR MORE INFORMATION ON OUR RANGE OF
RUBBER SHEET AND RUBBER PRODUCTS
VISIT WWW.POWELLINDUSTRIAL.COM.AU